

Technical Specifications

Symmetra PX 250kW Scalable to 500kW without Maintenance Bypass or Distribution-Parallel Capable | SY250K500D | Downloaded on 04/08/2024 (EST)



Symmetra PX 250kW Scalable to 500kW without Maintenance Bypass or Distribution-Parallel Capable

SY250K500D

Call for More Information 021 203 0606

- A high-performance, 3-phase, modular, scalable, power protection solution with industry-leading efficiency, capacity, and performance for medium to large data centers and mission-critical environments. Multiple UPSs can be installed in parallel for ultra-efficient system redundancy or up to 2MW of power protection. Parallel installations with custom switchgear and installations using a 3rd-party maintenance bypass panel require the APC Symmetra PX250/500 Third Party Switchgear Kit for breaker monitoring and EPO functionality.
- Includes: Assembly service, Installation guide, Network management card, Start-up service, User manual

Output	
Output power capacity	250.0kWatts / 250.0kVA
Max Configurable Power (Watts)	500.0kWatts / 500.0kVA
Nominal Output Voltage	400V 3PH, 480V 3PH
Output Voltage Distortion	Less than 2 %
Output Frequency (sync to mains)	50 Hz +/- 0.1 % For 50 Hz nominal Unsynchronised, 50 Hz Sync to mains, 60 Hz +/- 0.1 % For 60 Hz nominal Unsynchronised, 60 Hz Sync to mains
Other Output Voltages	415 V
Topology	Double conversion online
Waveform type	Sine wave
Overload Operation	10 minutes at 125% and 60 seconds at 150%
Output Connections	(1) Hard wire 5-wire (3P + N + E) (1) Hard wire 4-wire (3P + E)
Output Voltage THD	< 2% linear load and < 3% non-linear load
Output Voltage Tolerance	+/- 1% static and +/- 5% at 100% load step
Transfer Time	2 ms typical
Bypass	Built-in static bypass

Input	
Nominal Input Voltage	400V 3PH, 480V 3PH
Input frequency	40 - 70 Hz Auto-sensing

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Symmetra PX 250kW Scalable to 500kW without Maintenance Bypass or Distribution-Parallel Capable | SY250K500D | Downloaded on 04/08/2024 (EST)

Input	
Input Connections	Hard wire 4-wire (3P + E), Hard wire 5-wire (3P + N + E)
Input voltage range for main operations	340 - 460 (400 V), 408 - 552 (480 V)V
Input Total Harmonic Distortion	Less than 5 % for full load
Type of Input Protection Required	3-pole circuit breaker
Other Input Voltages	415 V
Maximum Short Circuit Withstand (Icw)	50.0kAmps
Input Power Factor at Full Load	0.99

Batteries & Runtime	
Battery type	VRLA
Included Battery Modules	16
Typical recharge time	8hour(s)
RBC Quantity	6
Battery Charge Power (Watts)	10.355kWatts
Extendable Run Time	1
Efficiency in Battery Operation	96.0 %
Overload Operation	10 minutes at 125% and 60 seconds at 150%
Runtime	View Runtime Graph (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	SYPX250-500_Parallel
Pre-Installed SmartSlot™ Cards	AP9635 (Available in Technical Tab on site)
Control panel	Touch screen LCD user interface
Emergency Power Off (EPO)	Optional
Available SmartSlot™ Interface Quantity	1

Physical	
Maximum Height	1991MM, 199.1CM
Maximum Width	3300MM, 330.0CM
Maximum Depth	1070MM, 107.0CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Net Weight	4542.0KG
Shipping weight	5003.0KG
Shipping Height	2150MM, 215.0CM
Shipping Width	1270MM, 127.0CM
Shipping Depth	4860MM, 486.0CM
Color	Black

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 1015.9meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	54.0dBA
Online thermal dissipation	30946.0BTU/hr
Protection Class	IP20, NEMA 1

Conformance	
Approvals	CSA C22.2 No 107.3-05, cUL listed, EN/IEC 62040-1-1, EN/IEC 62040-2, EN/IEC 62040-3, EUROBAT, UL 1778, UL 60950-1, UL listed
Standard warranty	1 year on-site repair or replace with factory authorized Start-Up

Sustainable Offer Status	
Proposition 65 Warning	Available in Documentation tab

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.